

PRODUCT INFORMATION PACKET

marathon®
Motors

Model No: 1009459-BR

Catalog No: 1009459

TerraMAX® Cast Iron Motor, 200 HP, 3 Ph, 60 Hz, 380 V, 1200 RPM, 315M/L Frame, TEFC



Regal and Marathon are trademarks of Regal Rexnord Corporation or one of its affiliated companies.
©2022 Regal Rexnord Corporation, All Rights Reserved. MC017097E

RegalRexnord

Nameplate Specifications

Output HP	200 Hp	Output KW	150.0 kW
Frequency	60 Hz	Voltage	380 V
Current	284.7 A	Speed	1192 rpm
Service Factor	1.25	Phase	3
Efficiency	95.8 %	Power Factor	0.82
Duty	S1	Insulation Class	F
Frame	315M/L	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Ambient Temperature	40 °C
Drive End Bearing Size	6319	Opp Drive End Bearing Size	6319
UL	No	CSA	No
CE	No	IP Code	55
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage	Starting Method	Direct On Line
Poles	6	Rotation	Clockwise
Mounting	B3	Motor Orientation	Horizontal
Drive End Bearing	C3	Opp Drive End Bearing	C3
Frame Material	Cast	Shaft Type	Keyed
Overall Length	1317 mm	Frame Length	840 mm
Shaft Diameter	80 mm	Shaft Extension	170 mm
Assembly/Box Mounting	TOP		
Outline Drawing	0231500895		

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:12/02/2022

OUTLINE




Model No. 1009459

Enclosure	U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [kgm]	T [Nm]	IE Class	Amb [°C]	Duty	Elevation [m]	Inertia [kg-m ²]	Weight [kg]
TEFC	380	Δ	60	150	200	284.7	1192	120.02	1176.98	IR3	40	S1	1000	26.58	1200

Motor Load Data

Load Point		NL	1/4FL	1/2FL	3/4FL	FL	5/4FL
Current	A	109.8	123.6	166.0	221.6	284.7	350.5
Torque	Nm	0.0	297.2	595.4	894.5	1177.0	1496.1
Speed	r/min	1200	1198	1196	1194	1192	1190
Efficiency	%	0.0	76.6	94.9	95.5	95.8	95.5
Power Factor	%	4.0	46.4	68.0	78.0	82.0	83.4


Performance vs Load Chart



Motor Speed Torque Data

Load Point		LR	P-Up	BD	Rated	NL
Speed	r/min	0	109	1097	1192	1200
Current	A	1992.9	1793.6	1046.0	284.7	109.8
Torque	pu	2.5	2.1	2.7	1	0

Starting Characteristics Chart



NOTE Refer data sheet for applicable standard and tolerances on performance parameters

Issued By

Issued Date