## Nameplate Specifications

Output HP	5 Hp	Output KW	3.7 kW
Frequency	60 Hz	Voltage	230 V
Current	21.7 A	Speed	1758 rpm
Service Factor	1	Phase	1
Efficiency	81.6 %	Power Factor	92
Duty	Continuous	Insulation Class	F
Design Code	L	KVA Code	Н
Frame	184TZ	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Ambient Temperature	40 °C
Drive End Bearing Size	6206	Opp Drive End Bearing Size	6205
UL	Recognized	CSA	Υ
CE	Υ	IP Code	55
Number of Speeds	1		

## **Technical Specifications**

Electrical Type	Capacitor Start Capacitor Run	Starting Method	Across The Line
Poles	4	Rotation	Selective Counterclockwise
Mounting	Rigid Base	Motor Orientation	Horizontal
Drive End Bearing	Ball	Opp Drive End Bearing	Ball
Frame Material	Rolled Steel	Shaft Type	Single Special Extension
Shaft Diameter	1.125 in	Assembly/Box Mounting	F1 ONLY
Outline Drawing	036145-1200	Connection Drawing	005018.01

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:11/01/2022