
PRODUCT INFORMATION PACKET

Model No: 141219.00 Catalog No: 141219.00 ...3HP..1200RPM.213T.TEFC.230/460V.3PH.60HZ.CONT.40C.1.15SF.RIGID......GENERAL PURPOSE......









Product Information Packet: Model No: 141219.00, Catalog No:141219.00 ...3HP..1200RPM.213T.TEFC.230/460V.3PH.60HZ.CONT.40C.1.15SF.RIGID......GENERAL PURPOSE......



Nameplate Specifications

Phase	3	Output HP	3 & 3 Hp
Output KW	2.2 & 2.2 kW	Voltage	208-230/460 & 190/380 V
Speed	1170 & 965 rpm	Service Factor	1.15 & 1.0
Frame	213T	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Efficiency	89.5 & 87.5 %
Ambient Temperature	40 °C	Frequency	60 & 50 Hz
Current	9.2-8.8/4.4 & 10/5 A	Power Factor	70
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	к
Drive End Bearing Size	6307	Opp Drive End Bearing Size	6206
UL	Recognized	CSA	Y
CE	Y	IP Code	43
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	6	Rotation	Reversible
Resistance Main	2.785 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	т	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	SS86560LE-965	Connection Drawing	EE7308LE

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/23/2023

Uncontrolled Copy

