PRODUCT INFORMATION PACKET



Model No: E547 Catalog No: E547 MODEL-IHP






Nameplate Specifications

Phase	3	Output HP	30.0 Hp
Output KW	22.4 kW	Voltage	200 V
Speed	1760 r/min	Service Factor	1.15
Frame	S286T	Enclosure	Drip Proof
Efficiency	92.4 %	Ambient Temperature	40 °C
Frequency	60 Hz	Current	86.5 A
Duty	Continuous	Insulation Class	F
UL	Recognized	CSA	Υ

Technical Specifications

Poles	4	Rotation	Counterclockwise
Drive End Bearing	311	Opp Drive End Bearing	207
Frame Length	14.00 in		
Connection Drawing	80022803.PCX		

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:02/05/2025



80022803-S01

NOTES:
1. DRAWING FOR REPRESENTATION ONLY, ACTUAL CONNECTION DIAGRAM IS COMPUTER GENERATED AND PRINTED ON ADHESIVE NAMEPLATE 800163.
2. RESERVED FOR THREE PHASE CONNECTIONS.

					UNLESS SPECIFIED			-6		DRAWN JVD 03-30-		-2021	
Γ					DEC.	INCHES	regal-beloit ((º/////	اعارو	<i>QL</i>	CHK	AJAY I	3-30	-2021
					.x	±.1		anna Erc	on b	APPD	AJAY (3-30-	-2021
					.xx	±.02	TITLE CONNECTION DIAGRAM			SCALE		1=1	
Γ					.xxx	±.005	1			REF	80	0228	
Γ	C UPDATED REGAL LOGO IN TITLE BLOCK JVD 03-30-2021			AJAY	.xxxx	±.0005	MAT'L.			FMF			
Ī	٧0.	REVISION	BY & DATE	CHK	ANG	±7'30"	FINISH			PREV			
	THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RICHTS OF DESIGN AND INVENTION ARE RESERVED.			RFP 03-30-2021 CAD FILE 80022803-S01				SIZE	DRAWING N		VGE C		REV.
L	THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				DIST LB-PR				8002	22803-S01		С	