



Nameplate Specifications

| | | | |
|------------------------|-------------------------|----------------------------|-----------------------------|
| Phase | 3 | Output HP | 7.50 & 5 Hp |
| Output KW | 5.6 & 3.7 kW | Voltage | 208-230/460 & 190/380 V |
| Speed | 1185 & 990 rpm | Service Factor | 1.15 & 1.15 |
| Frame | 254T | Enclosure | Totally Enclosed Fan Cooled |
| Thermal Protection | No Protection | Efficiency | 91.7 & 91.7 % |
| Ambient Temperature | 40 °C | Frequency | 60 & 50 Hz |
| Current | 23-22.2/11.1 & 19/9.5 A | Power Factor | 70 |
| Duty | Continuous | Insulation Class | F |
| Design Code | B | KVA Code | H |
| Drive End Bearing Size | 6309 | Opp Drive End Bearing Size | 6308 |
| UL | Recognized | CSA | Y |
| CE | Y | IP Code | 43 |
| Number of Speeds | 1 | | |

Technical Specifications

| | | | |
|-------------------|-----------------------------|-----------------------|---------------------|
| Electrical Type | Squirrel Cage Induction Run | Starting Method | Wye Start Delta Run |
| Poles | 6 | Rotation | Reversible |
| Mounting | Rigid Base | Motor Orientation | Horizontal |
| Drive End Bearing | Ball | Opp Drive End Bearing | Ball |
| Frame Material | Cast Iron | Shaft Type | T |
| Overall Length | 23.19 in | Shaft Diameter | 1.625 in |
| Shaft Extension | 4 in | Assembly/Box Mounting | F1/F2 CAPABLE |
| Outline Drawing | 16953860 | Connection Drawing | 004172.03 |