PRODUCT INFORMATION PACKET



Model No: 182TTFR6026 Catalog No: E2010A General Purpose Motor, 3 & 3 HP, 3 Ph, 60 & 50 Hz, 208-230/460 & 190/380 V, 1800 & 1500 RPM, 182TC Frame, TEFC



Product Information Packet: Model No: 182TTFR6026, Catalog No:E2010A General Purpose Motor, 3 & 3 HP, 3 Ph, 60 & 50 Hz, 208-230/460 & 190/380 V, 1800 & 1500 RPM, 182TC Frame, TEFC



Nameplate Specifications

| Phase | 3 | Output HP | 3 & 3 Hp |
|------------------------|---------------------|----------------------------|-----------------------------|
| Output KW | 2.2 & 2.2 kW | Voltage | 208-230/460 & 190/380 V |
| Speed | 1760 & 1450 rpm | Service Factor | 1.15 & 1.0 |
| Frame | 182TC | Enclosure | Totally Enclosed Fan Cooled |
| Thermal Protection | No Protection | Efficiency | 89.5 & 87.5 % |
| Ambient Temperature | 40 °C | Frequency | 60 & 50 Hz |
| Current | 8.4-8/4 & 9.2/4.6 A | Power Factor | 80 |
| Duty | Continuous | Insulation Class | F |
| Design Code | В | KVA Code | К |
| Drive End Bearing Size | 6207 | Opp Drive End Bearing Size | 6205 |
| UL | Recognized | CSA | Υ |
| CE | Υ | IP Code | 43 |
| Number of Speeds | 1 | | |
| | | | |

Technical Specifications

| Electrical Type | Squirrel Cage Induction Run | Starting Method | Across The Line |
|-----------------------|-----------------------------|-----------------------|-----------------|
| Poles | 4 | Rotation | Reversible |
| Resistance Main | 3.76 Ohms | Mounting | Rigid Base |
| Motor Orientation | Horizontal | Drive End Bearing | Ball |
| Opp Drive End Bearing | Ball | Frame Material | Rolled Steel |
| Shaft Type | Т | Overall Length | 16.19 in |
| Frame Length | 6.25 in | Shaft Diameter | 1.125 in |
| Shaft Extension | 2.75 in | Assembly/Box Mounting | F3 |
| Connection Drawing | A-EE7308 | Outline Drawing | A-SS68901-625 |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/21/2023

