

Nameplate Specifications

| | | | |
|------------------------|-----------------------------|----------------------------|------------|
| Output HP | 3 Hp | Output KW | 2.2 kW |
| Frequency | 60 Hz | Voltage | 208-230 V |
| Current | 13.8-12.8 A | Speed | 1760 rpm |
| Service Factor | 1.15 | Phase | 1 |
| Efficiency | 81.5 % | Power Factor | 92.5 |
| Duty | Continuous | Insulation Class | F |
| Design Code | NO DESIGN CODE | KVA Code | G |
| Frame | 184T | Enclosure | Drip Proof |
| Thermal Protection | Manual | Ambient Temperature | 40 °C |
| Drive End Bearing Size | 6206 | Opp Drive End Bearing Size | 6205 |
| UL | Recognized (Not Protector) | CSA | Y |
| CE | Y | IP Code | 22 |
| Number of Speeds | 1 | | |

Technical Specifications

| | | | |
|-----------------------|-------------------------------|-----------------------|----------------------------|
| Electrical Type | Capacitor Start Capacitor Run | Starting Method | Across The Line |
| Poles | 4 | Rotation | Selective Counterclockwise |
| Resistance Main | 0 Ohms | Mounting | Rigid Base |
| Motor Orientation | Horizontal | Drive End Bearing | Ball |
| Opp Drive End Bearing | Ball | Frame Material | Rolled Steel |
| Shaft Type | T | Overall Length | 14.19 in |
| Frame Length | 10.00 in | Shaft Diameter | 1.125 in |
| Shaft Extension | 2.81 in | Assembly/Box Mounting | F1 ONLY |
| Outline Drawing | 035696-1000 | Connection Drawing | 005056.03ME |