Nameplate Specifications

Output HP	5 Hp	Output KW	3.7 kW
Frequency	60 Hz	Voltage	575 V
Current	5.2 A	Speed	1760 rpm
Service Factor	1	Phase	3
Efficiency	87.5 %	Power Factor	81.6
Duty	Continuous	Insulation Class	Н
Design Code	INV	KVA Code	J
Frame	184TC	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Ambient Temperature	40 °C
Drive End Bearing Size	6206	Opp Drive End Bearing Size	6205
UL	Recognized	CSA	Υ
CE	Υ	IP Code	43
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Inverter Duty	Starting Method	Inverter Only	
Poles	4	Rotation	Reversible	
Resistance Main	3.08 Ohms	Mounting	Bolt-on Base	
Motor Orientation	Horizontal	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel	
Shaft Type	Т	Overall Length	13.97 in	
Frame Length	8.50 in	Shaft Diameter	1.125 in	
Shaft Extension	2.87 in	Assembly/Box Mounting	F3	
Inverter Load	CONSTANT 20:1			
Outline Drawing	035651-850	Connection Drawing	005102.01ME	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:05/18/2022						