

Nameplate Specifications

Output HP	3,1.33 Hp	Output KW	2.2 kW
Frequency	60 Hz	Voltage	460 V
Current	4.6,2.7 A	Speed	1760,1175 rpm
Service Factor	1.15	Phase	3
Efficiency	82.5 %	Power Factor	75.4
Duty	Continuous	Insulation Class	B
Design Code	2VT	KVA Code	K
Frame	184T	Enclosure	Drip Proof
Thermal Protection	No Protection	Ambient Temperature	40 °C
Drive End Bearing Size	6206	Opp Drive End Bearing Size	6203
UL	Recognized	CSA	Y
CE	Y	IP Code	22
Number of Speeds	2		

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	4//6	Rotation	Reversible
Resistance Main	6.32 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	T	Overall Length	13.72 in
Frame Length	6.75 in	Shaft Diameter	1.125 in
Shaft Extension	2.75 in	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	A-SS65625-675	Connection Drawing	A-EE7317