PRODUCT INFORMATION PACKET



Model No: 184TTFB6012 Catalog No: GT3412

Globetrotter® Close-Coupled Pump Motor, 5 & 3 HP, 3 Ph, 60 & 50 Hz, 230/460 & 190/380 V,

3600 & 3000 RPM, 184JP Frame, TEFC



Regal and Marathon are trademarks of Regal Rexnord Corporation or one of its affiliated companies. ©2023 Regal Rexnord Corporation, All Rights Reserved. MC017097E





Nameplate Specifications


Phase	3	Output HP	5 & 3 Hp
Output KW	3.7 & 2.2 kW	Voltage	230/460 & 190/380 V
Speed	3495 & 2920 rpm	Service Factor	1.15 & 1.15
Frame	184JP	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Efficiency	90.2 & 89.5 %
Ambient Temperature	40 °C	Frequency	60 & 50 Hz
Current	12/6 & 8.6/4.3 A	Power Factor	88.5
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	J
Drive End Bearing Size	6206	Opp Drive End Bearing Size	6205
UL	Recognized	CSA	Υ
CE	Υ	IP Code	43
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Inverter Rated	Starting Method	Line Or Inverter
Poles	2	Rotation	Reversible
Resistance Main	1.98 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	JP	Overall Length	20.04 in
Frame Length	6.73 in	Shaft Diameter	0.875 in
Shaft Extension	7.35 in	Assembly/Box Mounting	F1/F2 CAPABLE
Connection Drawing	EE7308	Outline Drawing	SS620562-184TC

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/22/2023

SS620562



						UNLES	ERANCES S SPECIFIED			DRAWN	ZXC 5-21-201
						DEC.		FEGAL REGAL-BELO	NT CORPORATION	СНК	
						.x	±.1			APPD	
						.xx	±.03	TITLE OUTLINE		SCALE	1=4
TTED 400TO	19.067					.xxx	±.005	TEFC-182/184JP-FR-R0	lled steel	REF	
TTFB 182TC	19.007					.xxxx	±.0005	MAT*L.		FMF	HWADA
TTFB 184TC	20.047	NO.	REVISION	BY & DATE	СНК	ANG	±1/2	FINISH		PREV	
<u> </u>			S DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED I		RFP			CAD FILE SS620562	SIZE DRAWING N		RE\
FRAME	C	"	CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESI THIS IS AN ELECTRONICALLY GENERATED DOCUMENT — DO NOT SCALE THIS PI		DIST				□B SS	62056	52



CERTIFICATION DATA SHEET

184TTFB6012 AA WINDING#: CHT18420005 NONE 1 Model#: CONN. DIAGRAM: EE7308 ASSEMBLY: F1/F2 CAPABLE

OUTLINE: SS620562

TYPICAL MOTOR PERFORMANCE DATA

HP	KW	SYNC. RPM	F.L. RPM	FRAME	ENCLOSURE	KVA CODE	DESIGN
5&3	3.70&2.24	3600	3495&2920	184JP	TEFC	J	В
]			ı——————			

	PH	Hz	VOLTS	FL AMPS	START TYPE	DUTY	INSL	S.F	AMB°C	ELEVATION
	3	60/50	230/460#190/	12/6&8.6/4.3	LINE OR	CONTINUOU	F7	1.15/1.15	40	3300
L			380		INVERTER	S				

FULL LOAD EFF: 90.2&89.5	3/4 LOAD EFF: 88.5	1/2 LOAD EFF: 86.5	GTD. EFF	ELEC. TYPE	NO LOAD AMPS
FULL LOAD PF: 88.5&85	3/4 LOAD PF: 84	1/2 LOAD PF: 74	87.5	SQ CAGE INV RATED	4.6 / 2.3

F.L. TORQUE	LOCKED ROTOR AMPS	L.R. TORQUE	B.D. TORQUE	F.L. RISE°C	
7.5 LB-FT	88 / 44	15.3 LB-FT 206	24.7 LB-FT 332	45	

SOUND PRESSURE @ 3 FT.	SOUND POWER	ROTOR WK^2	MAX. WK^2	SAFE STALL TIME	STARTS /HOUR	APPROX. MOTOR WGT
72 dBA	82 dBA	0.28 LB-FT^2	5 LB-FT^2	15 SEC.	2	110 LBS.

*** SUPPLEMENTAL INFORMATION ***

DE BRACKET TYPE	ODE BRACKET	MOUNT TYPE	ORIENTATION	SEVERE DUTY	HAZARDOUS LOCATION	DRIP COVER	SCREENS	PAINT
C-FACE	STANDARD	RIGID	HORIZONTAL	FALSE	NONE	FALSE	NONE	BLUE (ENAMEL)

BEARINGS		GREASE	SHAFT TYPE	SPECIAL DE	SPECIAL ODE	SHAFT	FRAME
DE	OPE					MATERIAL	MATERIAL
BALL	BALL	POLYREX EM	JP	NONE	NONE	1045 HOT	ROLLED STEEL
6206	6205					ROLLED (C-204)	

	THERMO-PF	ROTECTORS	THERMISTORS	CONTROL	SPACE /n HEATERS	
THERMOSTATS	PROTECTORS	WDG RTDs	BRG RTDs			
NONE	NOT	NONE	NONE	NONE	FALSE	NONE VOLTS

If Inverter equals NONE, contact factory for further information

INVERTER TORQUE: VARIABLE 10:1 INV. HP SPEED RANGE: NONE

ENCODER: NONE NONE NONE NONE NONE PPR

BRAKE: NONE NONE NONE P/N NONE NONE NONE

NONE FT-LB NONE V NONE Hz

Ν 0 Т Ε S

> DATE: 06/28/2017 06:52:49 AM FORM 3531 REV.3 02/07/99 ** Subject to change without notice.

