PRODUCT INFORMATION PACKET



Model No: 192042.30 Catalog No: 192042.30

Obsolete Replaced by 192042.00..3/4HP-0.55kW..1200RPM.D80.TEFC.230/460V.3PH.60HZ.CONT.40C..B3......

.....






Nameplate Specifications


Phase	3	Output HP	0.75 & 0.75 Hp
Output KW	0.56 & 0.56 kW	Voltage	230/460 & 200/400 V
Speed	1125 & 910 rpm	Service Factor	1.15 & 1.0
Frame	D80	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Efficiency	72 & 67 %
Ambient Temperature	40 °C	Frequency	60 & 50 Hz
Current	2.8/1.4 & 3.3/1.65 A	Power Factor	67
Duty	Continuous	Insulation Class	F
Design Code	NO DESIGN CODE	KVA Code	F
Drive End Bearing Size	6204	Opp Drive End Bearing Size	6204
UL	Recognized	CSA	Υ
CE	Υ	IP Code	55
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Inverter Rated	Starting Method	Line Or Inverter
Poles	6	Rotation	Reversible
Resistance Main	8.1 Ohms	Mounting	В3
Motor Orientation	Horizontal Or Up Or Down	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Aluminum
opp Billo Ella Boalling	Dan	i idilic Matchai	/ Wallington
Shaft Type	IEC	Assembly/Box Mounting	F3

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/22/2023





				UNLES	LERANCES S SPECIFIE				DRAWN	
				DEC.		REGAL REGAL-BELOIT CORPORATION		ON	CHK	
				.x	±.1	TITLE 230V / 460V connection drawing			APPD	
				.xx	±.03			SCALE		
				жхх	±.005	YY/Y -			REF	
				.xxx	±.0005	MAT'L.		FMF		
ND.	REVISION	BY & DATE	CHK	ANG	±1/2	FINISH			PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT		RFP CAD FILE		SIZE	DRAWING NO	3.	REV.			
IN CONNECTION VITH OUR VORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT			TZIG	•		•	1 B I			