PRODUCT INFORMATION PACKET



Model No: 199786.00 Catalog No: 199786.00

Obsolete Replaced by B199786.00..15..3600.215JP.ODP.230/460.3.60/50HZ.CONT.40C..RIGID C-FACE......

.....







Nameplate Specifications

Phase	3	Output HP	15 & 10 Hp
Output KW	11.2 & 7.5 kW	Voltage	230/460 & 190/380 V
Speed	3490 & 2917 rpm	Service Factor	1.15 & 1.15
Frame	215JP	Enclosure	Drip Proof
Thermal Protection	No Protection	Efficiency	91 & 89.5 %
Ambient Temperature	40 °C	Frequency	60 & 50 Hz
Current	35/17.5 & 28/14 A	Power Factor	88
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	F
Drive End Bearing Size	6309	Opp Drive End Bearing Size	6206
UL	Recognized	CSA	Υ
CE	Υ	IP Code	22
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Inverter Rated	Starting Method	Line Or Inverter
Poles	2	Rotation	Reversible
Resistance Main	.585 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	JP	Assembly/Box Mounting	F1/F2 CAPABLE
Inverter Load	VARIABLE 10:1		
Outline Drawing	SS620861	Connection Drawing	EE7308_LE

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/22/2023



