PRODUCT INFORMATION PACKET



Model No: 213TTGN14059 Catalog No: 213TTGN14059 7.5,1800,EPFC,213T,3/60/200/400





Nameplate Specifications

3	Output HP	7.50 Hp
5.6 kW	Voltage	200/400 V
1760 rpm	Service Factor	1.15
213T	Enclosure	Explosion Proof Fan cooled
Thermostat	Efficiency	89.5 %
50 ℃	Frequency	60 Hz
23.0/11.5 A	Power Factor	78
Continuous	Insulation Class	F
В	KVA Code	Н
6307	Opp Drive End Bearing Size	6208
No	CSA	N
N	IP Code	54
1	Hazardous Location	EXP PROOF CL I GR D CL II GR F&G T3B
	5.6 kW 1760 rpm 213T Thermostat 50 °C 23.0/11.5 A Continuous B 6307 No	5.6 kW Voltage 1760 rpm Service Factor 213T Enclosure Thermostat Efficiency 50 °C Frequency 23.0/11.5 A Power Factor Continuous Insulation Class B KVA Code 6307 Opp Drive End Bearing Size No CSA IP Code

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	4	Rotation	Reversible
Resistance Main	1.56 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	Т	Assembly/Box Mounting	F1 ONLY
Outline Drawing	B- 037660-912	Connection Drawing	A-EE7308T

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/07/2024

