## PRODUCT INFORMATION PACKET



Model No: 213TTGND12582 Catalog No: 213TTGND12582

3,1200,EPFC,213T,3/60/50/230/460#190/380





## Nameplate Specifications

3	Output HP	3 Hp
2.2 kW	Voltage	230/460 V
1175 rpm	Service Factor	1.15
213T	Enclosure	Explosion Proof Fan cooled
Thermostat	Efficiency	89.5 %
40 °C	Frequency	60 Hz
8.8/4.4 A	Power Factor	71.5
Continuous	Insulation Class	F
В	KVA Code	К
6307	Opp Drive End Bearing Size	6208
Recognized	CSA	N
N	IP Code	54
1	Hazardous Location	EXP PROOF CL I GR C&D T3B
	2.2 kW 1175 rpm 213T Thermostat 40 °C 8.8/4.4 A Continuous B 6307 Recognized	2.2 kW         Voltage           1175 rpm         Service Factor           213T         Enclosure           Thermostat         Efficiency           40 °C         Frequency           8.8/4.4 A         Power Factor           Continuous         Insulation Class           B         KVA Code           6307         Opp Drive End Bearing Size           Recognized         CSA           N         IP Code

## **Technical Specifications**

Electrical Type	Squirrel Cage Inverter Rated	Starting Method	Line Or Inverter	
Poles	6	Rotation	Reversible	
Resistance Main	2.7431 Ohms	Mounting	Rigid Base	
Motor Orientation	Horizontal	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Cast Iron	
Shaft Type	Т	Assembly/Box Mounting	F1 ONLY	
Outline Drawing	037660-912	Connection Drawing	EE7308T	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/07/2024



