

**Nameplate Specifications**

Phase	3	Output HP	1 Hp
Output KW	0.75 kW	Voltage	460 V
Speed	575 rpm	Service Factor	1
Frame	213TCVZ	Enclosure	Totally Enclosed Non Ventilated
Thermal Protection	Thermostat	Efficiency	69.5 %
Ambient Temperature	40 °C	Frequency	60 Hz
Current	3.9 A	Power Factor	37
Duty	10 Minute	Insulation Class	F
Design Code	B	KVA Code	K
Drive End Bearing Size	6309	Opp Drive End Bearing Size	6207
UL	No	CSA	Y
CE	Y	IP Code	54
Number of Speeds	1		

**Technical Specifications**

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	12	Rotation	Reversible
Resistance Main	6.78 Ohms	Mounting	Round
Motor Orientation	Shaft Down	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	Special Extension Both Sides	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	B-SS89981-725	Connection Drawing	A-EE7300DU

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:08/24/2023