PRODUCT INFORMATION PACKET



Model No: 215TTFW4015
Catalog No: U338
10 HP Close-Coupled Pump Motor, 3 phase, 3600 RPM, 575 V, 215JM Frame, TEFC

Close-Coupled Pump Motors



Product Information Packet: Model No: 215TTFW4015, Catalog No:U338 10 HP Close-Coupled Pump Motor, 3 phase, 3600 RPM, 575 V, 215JM Frame, TEFC



Nameplate Specifications

| Output HP | 10 Hp | Output KW | 7.5 kW |
|------------------------|------------|----------------------------|-----------------------------|
| Frequency | 60 Hz | Voltage | 575 V |
| Current | 9.6 A | Speed | 3525 rpm |
| Service Factor | 1.15 | Phase | 3 |
| Efficiency | 89.5 % | Power Factor | 87 |
| Duty | Continuous | Insulation Class | F |
| Design Code | В | KVA Code | G |
| Frame | 215JM | Enclosure | Totally Enclosed Fan Cooled |
| Thermal Protection | No | Ambient Temperature | 40 °C |
| Drive End Bearing Size | 6309 | Opp Drive End Bearing Size | 6206 |
| UL | Recognized | CSA | Υ |
| CE | Υ | IP Code | 43 |
| Number of Speeds | 1 | | |

Technical Specifications

| Electrical Type | Squirrel Cage Induction Run | Starting Method | Across The Line |
|-----------------------|-----------------------------|-----------------------|-----------------|
| Poles | 2 | Rotation | Reversible |
| Resistance Main | .98 Ohms | Mounting | Rigid Base |
| Motor Orientation | Horizontal | Drive End Bearing | Ball |
| Opp Drive End Bearing | Ball | Frame Material | Rolled Steel |
| Shaft Type | JM | Overall Length | 22.09 in |
| Frame Length | 11.15 in | Shaft Diameter | 0.875 in |
| Shaft Extension | 4.25 in | Assembly/Box Mounting | F1/F2 Capable |
| Connection Drawing | A-EE7300 | Outline Drawing | A-SS86629-1115 |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/12/2021



