PRODUCT INFORMATION PACKET



Model No: 215TTGCD16006 Catalog No: C306C 10,3600,EPFC,215TC,3/60/230/460





Nameplate Specifications

10 Hp	Output KW	7.5 kW
60 Hz	Voltage	230/460 V
23.6/11.8 A	Speed	3518 rpm
1	Phase	3
90.2 %	Power Factor	88
Continuous	Insulation Class	F
В	KVA Code	G
215TC	Enclosure	Explosion Proof Fan cooled
Thermostat	Ambient Temperature	40 °C
6309	Opp Drive End Bearing Size	6208
UL Listed; also, UL Certified for Canada	CSA	N
N	IP Code	54
EXP PROOF CL I GR C&D CL II GR F&G T3B	Number of Speeds	1
	60 Hz 23.6/11.8 A 1 90.2 % Continuous B 215TC Thermostat 6309 UL Listed; also, UL Certified for Canada N EXP PROOF CL I GR C&D CL II GR F&G	60 Hz Voltage 23.6/11.8 A Speed 1 Phase 90.2 % Power Factor Continuous Insulation Class B KVA Code 215TC Enclosure Thermostat Ambient Temperature 6309 Opp Drive End Bearing Size UL Listed; also, UL Certified for Canada CSA N IP Code EXP PROOF CL I GR C&D CL II GR F&G Number of Speeds

Technical Specifications

Electrical Type	Squirrel Cage Inverter Rated	Starting Method	Line Or Inverter
Poles	2	Rotation	Reversible
Resistance Main	1.218 Ohms	Mounting	Round
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	Т	Assembly/Box Mounting	F1 ONLY
Outline Drawing	037703-1212	Connection Drawing	EE7308T

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:01/19/2023



