PRODUCT INFORMATION PACKET



Model No: 215TTGN12503 Catalog No: 215TTGN12503 10.3600,EPFC,215T,3/60/230/460





Nameplate Specifications

	·	10 Hp
7.5 kW	Voltage	230/460 V
3535 rpm	Service Factor	1.15
215T	Enclosure	Explosion Proof Fan cooled
No Protection	Efficiency	91.7 %
50 °C	Frequency	60 Hz
23.6/11.8 A	Power Factor	87
Continuous	Insulation Class	F
В	KVA Code	Н
6307	Opp Drive End Bearing Size	6208
No	CSA	N
N	IP Code	54
1	Hazardous Location	EXP PROOF CL I GR D T2A
	3535 rpm 215T No Protection 50 °C 23.6/11.8 A Continuous B 6307 No	3535 rpm Service Factor 215T Enclosure No Protection Efficiency 50 °C Frequency 23.6/11.8 A Power Factor Continuous Insulation Class B KVA Code 6307 Opp Drive End Bearing Size No CSA N IP Code

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	2	Rotation	Reversible
Resistance Main	.8 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	Т	Assembly/Box Mounting	F1 ONLY
Outline Drawing	B- 037660-1212	Connection Drawing	A-EE7308

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/07/2024

