

Nameplate Specifications

| | | | |
|------------------------|-------------|----------------------------|-----------------------------|
| Output HP | 15 Hp | Output KW | 11.2 kW |
| Frequency | 60 Hz | Voltage | 230/460 V |
| Current | 37.5/18.8 A | Speed | 1775 rpm |
| Service Factor | 1.15 | Phase | 3 |
| Efficiency | 92.4 % | Power Factor | 81 |
| Duty | Continuous | Insulation Class | F |
| Design Code | B | KVA Code | G |
| Frame | 254T | Enclosure | Totally Enclosed Fan Cooled |
| Thermal Protection | No | Ambient Temperature | 40 °C |
| Drive End Bearing Size | 6309 | Opp Drive End Bearing Size | 6210 |
| UL | Recognized | CSA | Y |
| CE | Y | IP Code | 43 |
| Number of Speeds | 1 | | |

Technical Specifications

| | | | |
|-----------------------|-----------------------------|-----------------------|-----------------|
| Electrical Type | Squirrel Cage Induction Run | Starting Method | Across The Line |
| Poles | 4 | Rotation | Reversible |
| Resistance Main | .649 Ohms | Mounting | Rigid Base |
| Motor Orientation | Horizontal | Drive End Bearing | Ball |
| Opp Drive End Bearing | Ball | Frame Material | Cast Iron |
| Shaft Type | T | Overall Length | 23.52 in |
| Frame Length | 10.50 in | Shaft Diameter | 1.625 in |
| Shaft Extension | 4.2 in | Assembly/Box Mounting | F1/F2 CAPABLE |
| Outline Drawing | B-SS203015-1050 | Connection Drawing | A-EE7308 |