## PRODUCT INFORMATION PACKET



Model No: 256THTNA7031 Catalog No: 256THTNA7031 20,1800,TENV,256TC,3/60/230/460






## Nameplate Specifications


Phase	3	Output HP	20 Hp
Output KW	14.9 kW	Voltage	230/460 V
Speed	1775 rpm	Service Factor	1
Frame	256TC	Enclosure	Totally Enclosed Non Ventilated
Thermal Protection	Thermostat	Efficiency	91.7 %
Ambient Temperature	40 °C	Frequency	60 Hz
Current	54.0/27.0 A	Power Factor	74
Duty	Continuous	Insulation Class	F
Design Code	Α	KVA Code	К
Drive End Bearing Size	309	Opp Drive End Bearing Size	309
CSA	Υ	IP Code	43
Number of Speeds	1		

## **Technical Specifications**

Electrical Type	Squirrel Cage Inverter Duty	Starting Method	Inverter Only
Poles	4	Rotation	Reversible
Resistance Main	.275 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	Т	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	B-SS203233-1225	Connection Drawing	A-EE7308AD

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/07/2024





RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.