PRODUCT INFORMATION PACKET



Model No: 256TTDX4328
Catalog No: U220
20 HP Close-Coupled Pump Motor, 3 phase, 1800 RPM, 575 V, 256JP Frame, ODP
Close-Coupled Pump Motors

FRegalRexnord

Product Information Packet: Model No: 256TTDX4328, Catalog No:U220 20 HP Close-Coupled Pump Motor, 3 phase, 1800 RPM, 575 V, 256JP Frame, ODP



Nameplate Specifications

Output HP	20 Hp	Output KW	14.9 kW
Frequency	60 Hz	Voltage	575 V
Current	26.0 A	Speed	1760 rpm
Service Factor	1.15	Phase	3
Efficiency	91 %	Power Factor	79.3
Duty	Continuous	Insulation Class	В
Design Code	В	KVA Code	н
Frame	256JP	Enclosure	Drip Proof
Thermal Protection	No	Ambient Temperature	40 °C
Drive End Bearing Size	6309	Opp Drive End Bearing Size	6208
UL	Recognized	CSA	Υ
CE	Υ	IP Code	12
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	4	Rotation	Reversible
Resistance Main	.428 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	JP	Overall Length	27.04 in
Frame Length	15.15 in	Shaft Diameter	1.250 in
Shaft Extension	8.15 in	Assembly/Box Mounting	F1/F2 CAPABLE
Connection Drawing	A-EE7300	Outline Drawing	A-SS86519-1515

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/12/2021



