PRODUCT INFORMATION PACKET



Model No: 284TTDR14044 Catalog No: 284TTDR14044 25,1800,DP,284JPV,3/60/460PWS





Nameplate Specifications

Phase	3	Output HP	25 Hp	
Output KW	18.7 kW	Voltage	460 V	
Speed	1765 rpm	Service Factor	1.15	
Frame	284JPV	Enclosure	Drip Proof	
Thermal Protection	No Protection	Efficiency	91.7 %	
Ambient Temperature	40 °C	Frequency	60 Hz	
Current	30.5 A	Power Factor	84	
Duty	Continuous	Insulation Class	F	
Design Code	В	KVA Code	F	
Drive End Bearing Size	311	Opp Drive End Bearing Size	210	
UL	No	CSA	Υ	
CE	Υ	IP Code	22	
Number of Speeds	1			

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Part Wdg Start & Wye Start Delta Run
Poles	4	Rotation	Reversible
Resistance Main	.399 Ohms	Mounting	Round
Motor Orientation	Shaft Down	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	JP	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	B-SS301330-1250	Connection Drawing	A-EE7300BH

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:08/24/2023



