PRODUCT INFORMATION PACKET



Model No: 284TTFNA16826 Catalog No: 284TTFNA16826 20,1800,TEFC,284TC,3/60/460





Nameplate Specifications

3	Output HP	20 Hp
14.9 kW	Voltage	460 V
1775 rpm	Service Factor	1
284TC	Enclosure	Totally Enclosed Fan Cooled
No Protection	Efficiency	93 %
40 °C	Frequency	60 Hz
25.0 A	Power Factor	81
Continuous (S1)	Insulation Class	F
В	KVA Code	G
311	Opp Drive End Bearing Size	210
No	CSA	Υ
Υ	IP Code	56
1	Hazardous Location	ATEX ZONE 2 / ZONE 22
	14.9 kW 1775 rpm 284TC No Protection 40 °C 25.0 A Continuous (S1) B 311 No	14.9 kW Voltage 1775 rpm Service Factor 284TC Enclosure No Protection Efficiency 40 °C Frequency 25.0 A Power Factor Continuous (S1) Insulation Class B KVA Code 311 Opp Drive End Bearing Size No CSA Y IP Code

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line	
Poles	4	Rotation	Reversible	
Resistance Main	.305 Ohms	Mounting	Rigid Base	
Motor Orientation	Horizontal	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Cast Iron	
Shaft Type	Т	Assembly/Box Mounting	F3	
Outline Drawing	B-SS312188-1425	Connection Drawing	A-EE7300R	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:08/24/2023



