PRODUCT INFORMATION PACKET



Model No: 284TTTNA16033 Catalog No: 284TTTNA16033 25,1800,TEAO,284T,3/60/460





Nameplate Specifications

Phase	3	Output HP	25 Hp
Output KW	18.7 kW	Voltage	460 V
Speed	1775 r/min	Service Factor	1.15
Frame	284T	Enclosure	Totally Enclosed Air Over
Thermal Protection	No Protection	Efficiency	93.6 %
Ambient Temperature	40 °C	Frequency	60 Hz
Current	31.0 A	Power Factor	81
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	G
Drive End Bearing Size	6311	Opp Drive End Bearing Size	6210
UL	Recognized	CSA	Υ
CE	N	IP Code	43
Number of Speeds	1		
	·		

Technical Specifications

Electrical Type	Squirrel Cage Inverter Rated	Starting Method	Line Or Inverter	
Poles	4	Rotation	Reversible	
Resistance Main	.251 O	Mounting	Rigid Base	
Motor Orientation	Horizontal	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Cast Iron	
Shaft Type	Т	Assembly/Box Mounting	F1/F2 CAPABLE	
Outline Drawing	B-SS311162-1275	Connection Drawing	A-EE7300	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:04/08/2025



