
## **PRODUCT INFORMATION PACKET**

Model No: 286TTFNA16937 Catalog No: 286TTFNA16937 30,1800,TEFC,286TD,3/60/480





marathon<sup>®</sup>

Motors




## Nameplate Specifications


Phase	3	Output HP	30 Hp
Output KW	22.4 kW	Voltage	480 V
Speed	1773 rpm	Service Factor	1.15
Frame	286TD	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Efficiency	94.1 %
Ambient Temperature	40 °C	Frequency	60 Hz
Current	35.0 A	Power Factor	82
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	G
Drive End Bearing Size	6311	Opp Drive End Bearing Size	6210
UL	Recognized	CSA	Y
CE	Y	IP Code	54
Number of Speeds	1		

## **Technical Specifications**

Electrical Type	Squirrel Cage Inverter Rated	Starting Method	Line Or Inverter	
Poles	4	Rotation	Reversible	
Resistance Main	.205 Ohms	Mounting	Round	
Motor Orientation	Horizontal	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Cast Iron	
Shaft Type	т	Assembly/Box Mounting	F1/F2 CAPABLE	
Outline Drawing	B-SS311820H-1425	Connection Drawing	A-EE7300	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/24/2024





4 of 4