PRODUCT INFORMATION PACKET



Model No: 286TTGP11045 Catalog No: 286TTGP11045 30,1800,EPFC,286T,3/60/230/460





Nameplate Specifications

Phase	3	Output HP	30 Hp
Output KW	22.4 kW	Voltage	230/460 V
Speed	1768 rpm	Service Factor	1.15
Frame	286T	Enclosure	Explosion Proof Fan cooled
Thermal Protection	No Protection	Efficiency	92.4 %
Ambient Temperature	40 °C	Frequency	60 Hz
Current	74.0/37.0 A	Power Factor	82
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	G
Drive End Bearing Size	311	Opp Drive End Bearing Size	210
UL	No	CSA	N
CE	N	IP Code	56
Number of Speeds	1	Hazardous Location	EXP PROOF CL I GR D T2A

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line	
Poles	4	Rotation	Reversible	
Resistance Main	.285 Ohms	Mounting	Rigid Base	
Motor Orientation	Horizontal	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Cast Iron	
Shaft Type	Т	Assembly/Box Mounting	F1/F2 CAPABLE	
Outline Drawing	B-SS312123-1425	Connection Drawing	A-EE7308AG	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:08/24/2023



