## PRODUCT INFORMATION PACKET



Model No: 286TTGP11046 Catalog No: 286TTGP11046 30,1800,EPFC,286T,3/60/460





## Nameplate Specifications

3	Output HP	30 Hp
22.4 kW	Voltage	460 V
1768 rpm	Service Factor	1.15
286T	Enclosure	Explosion Proof Fan cooled
No Protection	Efficiency	92.4 %
45 °C	Frequency	60 Hz
37.0 A	Power Factor	82
Continuous	Insulation Class	F
В	KVA Code	G
311	Opp Drive End Bearing Size	210
No	CSA	N
N	IP Code	56
1	Hazardous Location	EXP PROOF CL I GR C&D T2A
	22.4 kW 1768 rpm 286T No Protection 45 °C 37.0 A Continuous B 311 No	22.4 kW Voltage  1768 rpm Service Factor  286T Enclosure No Protection Efficiency 45 °C Frequency 37.0 A Power Factor  Continuous Insulation Class B KVA Code 311 Opp Drive End Bearing Size No CSA N IP Code

## **Technical Specifications**

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line	
Poles	4	Rotation	Reversible	
Resistance Main	.285 Ohms	Mounting	Rigid Base	
Motor Orientation	Horizontal	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Cast Iron	
Shaft Type	Т	Assembly/Box Mounting	F1/F2 CAPABLE	
Outline Drawing	B-SS312123-1425	Connection Drawing	A-EE7300X	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:08/24/2023



