PRODUCT INFORMATION PACKET





marathon[®]

Regal and Marathon are trademarks of Regal Rexnord Corporation or one of its affiliated companies. ©2025 Regal Rexnord Corporation, All Rights Reserved. MC017097E


Nameplate Specifications

Phase	3	Output HP	10 Нр
Output KW	7.5 kW	Voltage	575 V
Speed	880 r/min	Service Factor	1.4
Frame	286T	Enclosure	Totally Enclosed Air Over
Thermal Protection	No Protection	Efficiency	89.5 %
Ambient Temperature	40 °C	Frequency	60 Hz
Current	13.6 A	Power Factor	61
Duty	Continuous	Insulation Class	F
Design Code	Α	KVA Code	н
Drive End Bearing Size	6311	Opp Drive End Bearing Size	6210
UL	Recognized	CSA	Y
CE	Ν	IP Code	43
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	8	Rotation	Reversible
Resistance Main	.63 O	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	т	Assembly/Box Mounting	F1/F2 CAPABLE
Connection Drawing	A-EE7300	Outline Drawing	B-SS311162-1425

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:04/08/2025



3 of 4

Uncontrolled Copy

