PRODUCT INFORMATION PACKET



Model No: 324TTGP11049 Catalog No: 324TTGP11049 40,1800,EPFC,324T,3/60/575





Nameplate Specifications

Phase	3	Output HP	40 Hp
Output KW	30.0 kW	Voltage	575 V
Speed	1765 rpm	Service Factor	1.15
Frame	324TZ	Enclosure	Explosion Proof Fan cooled
Thermal Protection	No Protection	Efficiency	93 %
Ambient Temperature	40 °C	Frequency	60 Hz
Current	40.0 A	Power Factor	80.5
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	G
Drive End Bearing Size	6312	Opp Drive End Bearing Size	6311
UL	No	CSA	N
CE	N	IP Code	54
Number of Speeds	1	Hazardous Location	EXP PROOF CL I GR D T2A

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line	
Poles	4	Rotation	Reversible	
Resistance Main	.17 Ohms	Mounting	Rigid Base	
Motor Orientation	Horizontal	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Cast Iron	
Shaft Type	Single Special Extension	Assembly/Box Mounting	F1 ONLY	
Outline Drawing	B-SS312173-1475	Connection Drawing	A-EE7300	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:08/24/2023



