
## **PRODUCT INFORMATION PACKET**







marathon<sup>®</sup>

Motors





## Nameplate Specifications

Phase	3	Output HP	50 Hp
Output KW	37.0 kW	Voltage	460 V
Speed	1765 rpm	Service Factor	1.15
Frame	326TC	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Efficiency	93 %
Ambient Temperature	40 °C	Frequency	60 Hz
Current	61.0 A	Power Factor	82
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	G
Drive End Bearing Size	312	Opp Drive End Bearing Size	311
UL	Recognized	CSA	Y
CE	Υ	IP Code	56
Number of Speeds	1		

## **Technical Specifications**

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	4	Rotation	Reversible
Resistance Main	.122 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	т	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	B-SS311829-1625	Connection Drawing	A-EE7300R

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/24/2024

