PRODUCT INFORMATION PACKET



Model No: 364THFCD39076 Catalog No: 364THFCD39076 40,1200,TEFC,364T,3/60/460





Nameplate Specifications

| Phase | 3 | Output HP | 40 Hp |
|------------------------|---------------|----------------------------|-----------------------------|
| Output KW | 30.0 kW | Voltage | 460 V |
| Speed | 1188 rpm | Service Factor | 1.15 |
| Frame | 364T | Enclosure | Totally Enclosed Fan Cooled |
| Thermal Protection | No Protection | Efficiency | 94.1 % |
| Ambient Temperature | 40 °C | Frequency | 60 Hz |
| Current | 48.0 A | Power Factor | 82.5 |
| Duty | Continuous | Insulation Class | Н |
| Design Code | В | KVA Code | G |
| Drive End Bearing Size | 6313 | Opp Drive End Bearing Size | 6213 |
| UL | Recognized | CSA | Υ |
| CE | Υ | IP Code | 56 |
| Number of Speeds | 1 | | |
| | | | |

Technical Specifications

| Electrical Type | Squirrel Cage Inverter Rated | Starting Method | Line Or Inverter |
|-----------------------|------------------------------|--------------------|----------------------------|
| Poles | 6 | Rotation | Selective Clockwise |
| Resistance Main | .1664 Ohms | Mounting | Rigid Base |
| Motor Orientation | Horizontal | Drive End Bearing | Ball |
| Opp Drive End Bearing | Ball | Frame Material | Cast Iron |
| Shaft Type | Т | Shaft Diameter | 2.375 in |
| Assembly/Box Mounting | F1/F2 CAPABLE | Inverter Load | CONSTANT 2:1/VARIABLE 10:1 |
| Outline Drawing | SS557662-364T | Connection Drawing | EE7300 |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:04/24/2023



