## PRODUCT INFORMATION PACKET



Model No: 365TTDS14011 Catalog No: 365TTDS14011 100,3600,DP,365JPV,3/60/416 PWS/YD





## Nameplate Specifications

Phase	3	Output HP	100 Hp	
Output KW	75.0 kW	Voltage	416 V	
Speed	3550 rpm	Service Factor	1.15	
Frame	365JPV	Enclosure	Drip Proof	
Thermal Protection	No Protection	Efficiency	93 %	
Ambient Temperature	40 °C	Frequency	60 Hz	
Current	133.0 A	Power Factor	83.5	
Duty	Continuous	Insulation Class	F	
Design Code	В	KVA Code	F	
Drive End Bearing Size	6313	Opp Drive End Bearing Size	6312	
UL	No	CSA	Υ	
CE	Υ	IP Code	12	
Number of Speeds	1			

## **Technical Specifications**

Electrical Type	Squirrel Cage Induction Run	Starting Method	Part Wdg Start & Wye Start Delta Run
Poles	2	Rotation	Reversible
Resistance Main	.064 Ohms	Mounting	Round
Motor Orientation	Shaft Down	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	JP	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	B-SS553704-1500	Connection Drawing	A-EE7300BH

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:08/24/2023



