PRODUCT INFORMATION PACKET



Model No: 365TTDS14056 Catalog No: 365TTDS14056 75,1800,DP,365TCZ,3/60/230/460





Nameplate Specifications

| Phase | 3 | Output HP | 75 Hp | |
|------------------------|---------------|----------------------------|------------|--|
| Output KW | 56.0 kW | Voltage | 230/460 V | |
| Speed | 1780 rpm | Service Factor | 1.15 | |
| Frame | 365TCZ | Enclosure | Drip Proof | |
| Thermal Protection | No Protection | Efficiency | 94.1 % | |
| Ambient Temperature | 40 °C | Frequency | 60 Hz | |
| Current | 179.0/89.5 A | Power Factor | 83.5 | |
| Duty | Continuous | Insulation Class | F | |
| Design Code | В | KVA Code | G | |
| Drive End Bearing Size | 6314 | Opp Drive End Bearing Size | 6312 | |
| UL | Recognized | CSA | Υ | |
| CE | Υ | IP Code | 12 | |
| Number of Speeds | 1 | | | |
| | | | | |

Technical Specifications

| Electrical Type | Squirrel Cage Induction Run | Starting Method | Across The Line |
|-----------------------|-----------------------------|-----------------------|-----------------|
| Poles | 4 | Rotation | Reversible |
| Resistance Main | .085 Ohms | Mounting | Rigid Base |
| Motor Orientation | Horizontal | Drive End Bearing | Ball |
| Opp Drive End Bearing | Ball | Frame Material | Cast Iron |
| Shaft Type | Single Special Extension | Assembly/Box Mounting | F1/F2 CAPABLE |
| Outline Drawing | B-SS553699-1500 | Connection Drawing | A-EE7308K |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:08/24/2023



