

PRODUCT INFORMATION PACKET





marathon[®]

Motors



©2023 Regal Rexnord Corporation, All Rights Reserved. MC017097E



Nameplate Specifications

Phase	3	Output HP	100 Hp
Output KW	75.0 kW	Voltage	460 V
Speed	1190 rpm	Service Factor	1
Frame	444T	Enclosure	Totally Enclosed Blower cooled - Axial
Thermal Protection	No Protection	Efficiency	95.4 %
Ambient Temperature	40 °C	Frequency	60 Hz
Current	120.0 A	Power Factor	82
Duty	Continuous	Insulation Class	н
Design Code	Α	KVA Code	G
Drive End Bearing Size	6318	Opp Drive End Bearing Size	6316
UL	Recognized	CSA	Y
CE	Y	IP Code	54
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Inverter Duty	Starting Method	Inverter Only
Poles	6	Rotation	Reversible
Resistance Main	.042 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	т	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	B-SS555214-2025	Connection Drawing	A-EE7300DR

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:08/24/2023

