

Nameplate Specifications

| | | | |
|------------------------|---------------|----------------------------|-----------------------------|
| Output HP | 125 Hp | Output KW | 93.0 kW |
| Frequency | 60 Hz | Voltage | 460 V |
| Current | 140.0 A | Speed | 1790 rpm |
| Service Factor | 1.15 | Phase | 3 |
| Efficiency | 95.4 % | Power Factor | 87.5 |
| Duty | Continuous | Insulation Class | H |
| Design Code | B | KVA Code | G |
| Frame | 444T | Enclosure | Totally Enclosed Fan Cooled |
| Thermal Protection | No Protection | Ambient Temperature | 40 °C |
| Drive End Bearing Size | 6319 | Opp Drive End Bearing Size | 6317 |
| UL | Recognized | CSA | Y |
| CE | Y | IP Code | 55 |
| Number of Speeds | 1 | | |

Technical Specifications

| | | | |
|-----------------------|------------------------------|-------------------|---------------------|
| Electrical Type | Squirrel Cage Inverter Rated | Starting Method | Line Or Inverter |
| Poles | 4 | Rotation | Selective Clockwise |
| Resistance Main | .0374 Ohms | Mounting | Rigid Base |
| Motor Orientation | Horizontal | Drive End Bearing | Ball |
| Opp Drive End Bearing | Ball | Frame Material | Cast Iron |
| Shaft Type | T | Shaft Diameter | 3.375 in |
| Assembly/Box Mounting | F1/F2 CAPABLE | | |
| Connection Drawing | EE7300U | Outline Drawing | SS557668 |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/05/2022