
PRODUCT INFORMATION PACKET

Model No: 444TTGN18502 Catalog No: 444TTGN18502 125,3600,EPFC,444TCVZ,3/60/460





1 of 4




Nameplate Specifications

Phase	3	Output HP	125 Нр
Output KW	93.0 kW	Voltage	460 V
Speed	3570 rpm	Service Factor	1.15
Frame	444TCVZ	Enclosure	Explosion Proof Fan cooled
Thermal Protection	No Protection	Efficiency	95.4 %
Ambient Temperature	55 °C	Frequency	60 Hz
Current	140.0 A	Power Factor	87.5
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	G
Drive End Bearing Size	6314	Opp Drive End Bearing Size	6313
UL	No	CSA	N
CE	Ν	IP Code	54
Number of Speeds	1	Hazardous Location	EXP PROOF CL I GR C&D T2A

Technical Specifications

Electrical Type	Squirrel Cage Inverter Rated	Starting Method	Line Or Inverter
Poles	2	Rotation	Reversible
Resistance Main	.022 Ohms	Mounting	Round
Motor Orientation	Shaft Down	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	Single Special Extension	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	B-SS552137-2025	Connection Drawing	A-EE7300U

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/24/2024



12/2 You created this PDF from an application that is not licensed to print to novaPDF printer (http://www.novapdf.com) 3 of 4

