PRODUCT INFORMATION PACKET

Model No: 445TTDS16055 Catalog No: 445TTDS16055 200,1800,DP,445TDZ,3/60/460YD





1 of 4

Product Information Packet: Model No: 445TTDS16055, Catalog No:445TTDS16055 200,1800,DP,445TDZ,3/60/460YD


Nameplate Specifications

Output HP	200 Нр	Output KW	149.0 kW
Frequency	60 Hz	Voltage	460 V
Current	225.0 A	Speed	1785 rpm
Service Factor	1.15	Phase	3
Efficiency	95.8 %	Power Factor	86.5
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	G
Frame	445TDZ	Enclosure	Drip Proof
Thermal Protection	No Protection	Ambient Temperature	46 °C
Drive End Bearing Size	NU221	Opp Drive End Bearing Size	6316
UL	Recognized	CSA	Y
CE	Y	IP Code	12
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Wye Start Delta Run
Poles	4	Rotation	Reversible
Resistance Main	.021 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Roller
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	Single Special Extension	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	B-SS513759-2050	Connection Drawing	A-EE7340

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/02/2022



3 of 4



