



### Nameplate Specifications

Phase	<b>3</b>	Output HP	<b>250 Hp</b>
Output KW	<b>187.0 kW</b>	Voltage	<b>460 V</b>
Speed	<b>1190 rpm</b>	Service Factor	<b>1</b>
Frame	<b>447/449TR</b>	Enclosure	<b>Totally Enclosed Non Ventilated</b>
Thermal Protection	<b>Thermostat</b>	Efficiency	<b>95.4 %</b>
Ambient Temperature	<b>50 °C</b>	Frequency	<b>60 Hz</b>
Current	<b>302.0 A</b>	Power Factor	<b>81</b>
Duty	<b>60 Minute</b>	Insulation Class	<b>H</b>
Design Code	<b>A</b>	KVA Code	<b>K</b>
Drive End Bearing Size	<b>6319</b>	Opp Drive End Bearing Size	<b>6318</b>
UL	<b>Recognized</b>	CSA	<b>Y</b>
CE	<b>Y</b>	IP Code	<b>54</b>
Number of Speeds	<b>1</b>		

### Technical Specifications

Electrical Type	<b>Squirrel Cage Inverter Duty</b>	Starting Method	<b>Inverter Only</b>
Poles	<b>6</b>	Rotation	<b>Reversible</b>
Resistance Main	<b>.01 Ohms</b>	Mounting	<b>Rigid Base</b>
Motor Orientation	<b>Horizontal</b>	Drive End Bearing	<b>Ball</b>
Opp Drive End Bearing	<b>Ball</b>	Frame Material	<b>Cast Iron</b>
Shaft Type	<b>Special Extension Both Sides</b>	Assembly/Box Mounting	<b>F1/F2 CAPABLE</b>
Outline Drawing	<b>B-SS553245-2875</b>	Connection Drawing	<b>A-EE7300S</b>

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/07/2024