
## **PRODUCT INFORMATION PACKET**







marathon<sup>®</sup>

Motors





## Nameplate Specifications

Phase	3	Output HP	60 Hp
Output KW	45.0 kW	Voltage	460 V
Speed	888 rpm	Service Factor	1
Frame	447/449TR	Enclosure	Totally Enclosed Non Ventilated
Thermal Protection	Thermostat	Efficiency	94.1 %
Ambient Temperature	40 °C	Frequency	60 Hz
Current	83.5 A	Power Factor	71
Duty	Continuous	Insulation Class	н
Design Code	INV	KVA Code	н
Drive End Bearing Size	6319	Opp Drive End Bearing Size	6318
UL	Recognized	CSA	Y
CE	Υ	IP Code	54
Number of Speeds	1		

## **Technical Specifications**

Electrical Type	Squirrel Cage Inverter Duty	Starting Method	Inverter Only
Poles	8	Rotation	Reversible
Resistance Main	.065 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	Special Extension Both Sides	Assembly/Box Mounting	F1 ONLY
Outline Drawing	B-SS555785-2875	Connection Drawing	A-EE7300AK

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:08/24/2023

