PRODUCT INFORMATION PACKET



Model No: 5010SVDSL16002 Catalog No: Y9115 ndurance Series® MODEL-IHP, 700HP,2P,ODP,5010S,3/60/2300/4000-4160,CW/DE,120VSH,WRTD-SH,BRTD PROV



Regal and Marathon are trademarks of Regal Rexnord Corporation or one of its affiliated companies. ©2023 Regal Rexnord Corporation, All Rights Reserved. MC017097E



Product Information Packet: Model No: 5010SVDSL16002, Catalog No:Y9115 Endurance Series® MODEL-IHP, 700HP,2P,ODP,5010S,3/60/2300/4000-4160,CW/DE,120VSH,WRTD-SH,BRTD PROV

marathon®


Nameplate Specifications


Phase	3	Output HP	700 Hp
Output KW	520.0 kW	Voltage	2300/4000-4160 V
Speed	3578 rpm	Service Factor	1.15
Frame	5010S	Enclosure	Drip Proof
Thermal Protection	No Protection	Efficiency	95.4 %
Ambient Temperature	40 °C	Frequency	60 Hz
Current	152.0/87.5-84.0 A	Power Factor	90.5
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	G
Drive End Bearing Size	6316	Opp Drive End Bearing Size	6316
UL	Recognized	CSA	Y
CE	N	IP Code	23
Number of Speeds	1		

Technical Specifications

Electrical Type	Bar Rotator Induction Run	Starting Method	Across The Line
Poles	2	Rotation	Fixed Counterclockwise
Mounting	Rigid Base	Motor Orientation	Horizontal
Drive End Bearing	Ball	Opp Drive End Bearing	Ball
Frame Material	Cast Iron	Shaft Type	S
Shaft Diameter	2.875 in	Assembly/Box Mounting	F1/F2 CAPABLE
Connection Drawing	EE7304AC	Outline Drawing	MCA8250

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:12/12/2023





8/26/2007 7:28:24 PM -

ERROR: syntaxerror OFFENDING COMMAND: --nostringval--

STACK:

-dictionary--dictionary-/Pscript_WinNT_Compat -dictionary-

