


PRODUCT INFORMATION PACKET

rotor nl®

Model No: 6RN112M06E36U463041

Catalog No: 6RN112M06E36U46@3041

3.00 kW General Purpose Low Voltage IEC Motor IE3, 3 phase, 1000 rpm, D400/Y690V 50Hz,
112M Frame B5, IC411



Regal and Rotor nl are trademarks of Regal Rexnord Corporation or one of its affiliated companies.
©2022 Regal Rexnord Corporation, All Rights Reserved. MC017097E

RegalRexnord®



Nameplate Specifications

Output HP	4 Hp	Output KW	3.0 kW
Frequency	50 Hz	Voltage	D400/Y690 V
Current	6.80 A	Speed	965 rpm
Service Factor	1	Phase	3
Efficiency	85.6 %	Power Factor	0.74
Duty	S1	Insulation Class	F
Frame	112M	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Ambient Temperature	40 °C
Drive End Bearing Size	6306-2Z/C3WT (-40°C/+160°C)	Opp Drive End Bearing Size	6306-2Z/C3WT (-40°C/+160°C)
UL	No	CSA	Optional
CE	Yes	IP Code	IP55
Number of Speeds	1	Efficiency Class	IE3

Technical Specifications

Electrical Type	Squirrel Cage	Starting Method	Direct On Line
Poles	6	Rotation	Clockwise Shaft End
Mounting	B5	Motor Orientation	Any
Frame Material	Cast iron	Shaft Type	Keyed
Outline Drawing	6RN112M06E36U463041		

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:12/02/2022


Model No. 6-Pole cage motor 6RN 112M 3kW D400V 50Hz IM1081

U (V)	Δ / Y Conn	f [Hz]	P		I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
			[kW]	[hp]					FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	3	4	6,8	965	29,7	IE3	85,6			0,74			5,50	2,00	2,70
690	Y				3,93												

Motor type	6RN112M06E36
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	112M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	3 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise winding	56 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Rotor type	Cage motor
Bearing type	Rolling element bearing 6306-2Z/C3WT - 6306-2Z/C3WT
Type of grease	Unirex N3
Phase resistance at 20°C	4,7800 Ohm
Country of origin	CZ

Degree of protection	IP55
Mounting type	IM1081
Cooling method	IC411
Motor weight - approx.	46 kg
Gross weight - approx.	47 kg
Vibration level	according IEC60034-14
Starting method	d.o.l.
Direction of rotation	cw /ccw
Paint shade	RAL 7030
Terminal box position	Top - Pos 3

Torques	Locked rotor	At start	Pull-up	Breakdown	No-load
@400V 50Hz	200%			270%	



NOTE

All performance values at rated voltage and frequency.
 All performance parameters are subjected to standard tolerance as per IEC 60034-1
 Voltage, Frequency are as per IEC60034-1
 Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



This is an uncontrolled copy, data can be changed anytime.

