Product Information Packet: Model No: CPE31, Catalog No:CPE31 7.5 HP Close-Coupled Pump Motor, 3 phase, 1800 RPM, 208-230/460 V, 213JP Frame, TEFC



Nameplate Specifications

Output HP	7.5 Hp	Output KW	5.6 kW
Frequency	60 Hz	Voltage	208-230/460 V
Current	9.5 A	Speed	1768 rpm
Service Factor	1.15	Phase	3
Duty	Continuous	Insulation Class	F
Frame	213JP	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	None	Ambient Temperature	40 °C
UL	Recognized	CSA	Y
Number of Speeds	1		

Technical Specifications

Electrical Type	POLYPHASE	Starting Method	Across The Line	
Poles	4	Rotation	Reversible	
Mounting	Rigid Base	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Cast Iron	
Shaft Type	Keyed	Overall Length	23.67 in	
Frame Length	7.24 in	Shaft Diameter	1.750 in	
Shaft Extension	8.14 in			
Connection Drawing	A-EE7308	Outline Drawing	SS620620	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/12/2021