Product Information Packet: Model No: CPE40, Catalog No:CPE40 15 HP Close-Coupled Pump Motor, 3 phase, 1800 RPM, 208-230/460 V, 254JM Frame, TEFC



## Nameplate Specifications

Output HP	15 Hp	Output KW	11.2 kW
Frequency	60 Hz	Voltage	208-230/460 V
Current	41.6-37.6/18.8 A	Speed	1775 rpm
Service Factor	1.15	Phase	3
Duty	Continuous	Insulation Class	F
Frame	254JM	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	None	Ambient Temperature	40 °C
UL	Recognized	CSA	Y
CE	Y	Number of Speeds	1

## **Technical Specifications**

Electrical Type	POLYPHASE	Starting Method	Across The Line	
Poles	4	Rotation	Reversible	
Mounting	Rigid Base	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Cast Iron	
Shaft Type	Keyed	Overall Length	26.60 in	
Frame Length	11.41 in	Shaft Diameter	1.750 in	
Shaft Extension	5.25 in			
Connection Drawing	A-EE7308K	Outline Drawing	SS620564	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/12/2021