Product Information Packet: Model No: CPO45A, Catalog No:CPO45A 7.5 HP Close-Coupled Pump Motor, 3 phase, 3600 RPM, 230/460 V, 184J Frame, ODP



Nameplate Specifications

Output HP	7.5 Нр	Output KW	5.6 kW
Frequency	60 Hz	Voltage	230/460 V
Current	17.8/8.9 A	Speed	3510 rpm
Service Factor	1.15	Phase	3
Duty	Continuous	Insulation Class	F
Frame	184J	Enclosure	Drip Proof
Thermal Protection	None	Ambient Temperature	40 °C
UL	Recognized	CSA	Y
CE	Y	Number of Speeds	1
Duty Frame Thermal Protection UL	Continuous 184J None Recognized	Insulation Class Enclosure Ambient Temperature CSA	F Drip Proof 40 °C

Technical Specifications

Electrical Type	POLYPHASE	Starting Method	Across The Line	
Poles	2	Rotation	Reversible	
Mounting	Rigid Base	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel	
Shaft Type	Keyed	Overall Length	15.64 in	
Frame Length	8.26 in	Shaft Diameter	1.249 in	
Shaft Extension	4.25 in			
Connection Drawing	EE7308	Outline Drawing	SS600204	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/12/2021