## Product Information Packet: Model No: E3AC3002091B50S41100, Catalog No:E3AC3002091B50S41100 Made in Italy E3AC30 Series, General Purpose Low Voltage IEC motor IE3, Flameproof, 1,50kW, 3 phase, 2870 RPM, D230/Y400V 50Hz, 90S Frame B5, 2 Poles, IC411

## Nameplate Specifications

Phase	3	Output HP	2 Нр
Output KW	1.5 kW	Voltage	230/400 V
Speed	2870 rpm	Service Factor	1
Frame	90S	Enclosure	Totally Enclosed Fan Cooled
Efficiency	84.8 %	Ambient Temperature	40 °C
Frequency	50 Hz	Current	3.0 A
Power Factor	0.84	Duty	S1
Insulation Class	F	Drive End Bearing Size	6205
Opp Drive End Bearing Size	6205	UL	No
CSA	No	CE	Yes
IP Code	IP55	Number of Speeds	1

## **Technical Specifications**

Electrical Type	Squirrel Cage	Starting Method	Direct On Line	
Poles	2	Rotation	Bi-Directional	
Mounting	B5	Motor Orientation	Horizontal	
Drive End Bearing	Zz	Opp Drive End Bearing	Zz	
Frame Material	Cast Iron	Shaft Type	Keyed	
Overall Length	422.50 mm	Frame Length	190.00 mm	
Shaft Diameter	24.000 mm	Shaft Extension	50 mm	
Assembly/Box Mounting	Тор			
Outline Drawing	B5A04E8095001B01	Connection Drawing	SC-01-T-1v-1a	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:05/03/2023