Product Information Packet: Model No: E3AC3002223B35D41100, Catalog No:E3AC3002223B35D41100 Made in Italy E3AC30 Series, General Purpose Low Voltage IEC motor IE3, Flameproof, 45,00kW, 3 phase, 2976 RPM, D400/Y690V 50Hz, 225SM Frame B35, 2 Poles, IC411

Nameplate Specifications

Phase	3	Output HP	60.0 Hp
Output KW	45.0 kW	Voltage	400/690 V
Speed	2976 rpm	Service Factor	1
Frame	225SM	Enclosure	Totally Enclosed Fan Cooled
Efficiency	94 %	Ambient Temperature	40 °C
Frequency	50 Hz	Power Factor	0.89
Duty	S 1	Insulation Class	F
Drive End Bearing Size	6313	Opp Drive End Bearing Size	6313
UL	No	CSA	No
CE	Yes	IP Code	IP55
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage	Starting Method	Direct On Line
Poles	2	Rotation	Bi-Directional
Mounting	B35	Motor Orientation	Horizontal
Drive End Bearing	Zz C3	Opp Drive End Bearing	Zz C3
Frame Material	Cast Iron	Shaft Type	Keyed
Overall Length	1011.00 mm	Frame Length	480.00 mm
Shaft Diameter	60.000 mm	Shaft Extension	140 mm
Assembly/Box Mounting	Тор		
Connection Drawing	SC-01-T-1v-1a	Outline Drawing	B3A04E8225001D01

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/10/2023