Product Information Packet: Model No: E3AC3004163B35D41100, Catalog No:E3AC3004163B35D41100 Made in Italy E3AC30 Series, General Purpose Low Voltage IEC motor IE3, Flameproof, 11,00kW, 3 phase, 1476 RPM, D400/Y690V 50Hz, 160MB Frame B35, 4 Poles, IC411

Nameplate Specifications

Phase	3	Output HP	15.0 Hp
Output KW	11.0 kW	Voltage	400/690 V
Speed	1476 rpm	Service Factor	1
Frame	160MB	Enclosure	Totally Enclosed Fan Cooled
Efficiency	91.4 %	Ambient Temperature	40 °C
Frequency	50 Hz	Power Factor	0.84
Duty	S1	Insulation Class	F
Drive End Bearing Size	6309	Opp Drive End Bearing Size	6309
UL	No	CSA	Yes
CE	Yes	IP Code	IP55
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage	Starting Method	Direct On Line
Poles	4	Rotation	Bi-Directional
Mounting	B35	Motor Orientation	Horizontal
Drive End Bearing	Zz C3	Opp Drive End Bearing	Zz C3
Frame Material	Cast Iron	Shaft Type	Keyed
Overall Length	853.00 mm	Frame Length	370.00 mm
Shaft Diameter	42.000 mm	Shaft Extension	110 mm
Assembly/Box Mounting	Тор		
Outline Drawing	B3A04E8165001D01	Connection Drawing	SC-01-T-1v-1a

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/10/2023