Product Information Packet: Model No: E3AC3004257B35D41100, Catalog No:E3AC3004257B35D41100 Made in Italy E3AC30 Series, General Purpose Low Voltage IEC motor IE3, Flameproof, 75,00kW, 3 phase, 1489 RPM, D400/Y690V 50Hz, 250MB Frame B35, 4 Poles, IC411, Higher Output Motor

Nameplate Specifications

Phase	3	Output HP	100.0 Hp
Output KW	75.0 kW	Voltage	400/690 V
Speed	1489 rpm	Service Factor	1
Frame	250MB	Enclosure	Totally Enclosed Fan Cooled
Efficiency	95 %	Ambient Temperature	40 °C
Frequency	50 Hz	Power Factor	0.87
Duty	S1	Insulation Class	F
Drive End Bearing Size	6314	Opp Drive End Bearing Size	6313
UL	No	CSA	No
CE	Yes	IP Code	IP55
Number of Speeds	1		

Technical Specifications

Squirrel Cage	Starting Method	Direct On Line
4	Rotation	Bi-Directional
B35	Motor Orientation	Horizontal
Zz C3	Opp Drive End Bearing	Zz C3
Cast Iron	Shaft Type	Keyed
1197.00 mm	Frame Length	560.00 mm
65.000 mm	Shaft Extension	140 mm
Тор		
SC-01-T-1v-1a	Outline Drawing	B3A04E8250011D01
	4 B35 Zz C3 Cast Iron 1197.00 mm 65.000 mm	4 Rotation B35 Motor Orientation Zz C3 Opp Drive End Bearing Cast Iron Shaft Type 1197.00 mm Frame Length 65.000 mm Shaft Extension Top

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/10/2023