Product Information Packet: Model No: E3AC3004351B35D41100, Catalog No:E3AC3004351B35D41100 Made in Italy E3AC30 Series, General Purpose Low Voltage IEC motor IE3, Flameproof, 250,00kW, 3 phase, 1491 RPM, D400/Y690V 50Hz, 355M Frame B35, 4 Poles, IC411

## Nameplate Specifications

Phase	3	Output HP	335.0 Hp
Output KW	250.0 kW	Voltage	400/690 V
Speed	1491 rpm	Service Factor	1
Frame	355M	Enclosure	Totally Enclosed Fan Cooled
Efficiency	96 %	Ambient Temperature	40 °C
Frequency	50 Hz	Power Factor	0.89
Duty	S1	Insulation Class	F
Drive End Bearing Size	6322	Opp Drive End Bearing Size	6316
UL	No	CSA	No
CE	Yes	IP Code	IP55
Number of Speeds	1		

## **Technical Specifications**

Electrical Type	Squirrel Cage	Starting Method	Direct On Line
Poles	4	Rotation	Bi-Directional
Mounting	B35	Motor Orientation	Horizontal
Drive End Bearing	C3	Opp Drive End Bearing	C3
Frame Material	Cast Iron	Shaft Type	Keyed
Overall Length	1844.00 mm	Frame Length	935.00 mm
Shaft Diameter	100.000 mm	Shaft Extension	210 mm
Assembly/Box Mounting	Тор		
Outline Drawing	B3A048355021D01	Connection Drawing	SC-01-T-1v-1a

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/10/2023