

Nameplate Specifications

Phase	3	Output HP	500.0 Hp
Output KW	375.0 kW	Voltage	400/690 V
Speed	1489 rpm	Service Factor	1
Frame	355LD	Enclosure	Totally Enclosed Fan Cooled
Efficiency	96 %	Ambient Temperature	40 °C
Frequency	50 Hz	Power Factor	0.9
Duty	S1	Insulation Class	F
Drive End Bearing Size	6322	Opp Drive End Bearing Size	6316
UL	No	CSA	No
CE	Yes	IP Code	IP55
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage	Starting Method	Direct On Line
Poles	4	Rotation	Bi-Directional
Mounting	B35	Motor Orientation	Horizontal
Drive End Bearing	C3	Opp Drive End Bearing	C3
Frame Material	Cast Iron	Shaft Type	Keyed
Overall Length	1994.00 mm	Frame Length	1085.00 mm
Shaft Diameter	100.000 mm	Shaft Extension	210 mm
Assembly/Box Mounting	Top		
Connection Drawing	SC-01-T-1v-1a	Outline Drawing	B3A048350021D01

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/10/2023